



7X7 Stainless Steel Cable

Diameter (in)	Weight per 100ft (lbs)	Nominal B.S. (lbs)	
		AISI 302,304	AISI 316
1/16	0.75	480	420
3/32	1.60	920	810
1/8	2.80	1,700	1,510
5/32	4.30	2,500	2,270
3/16	6.20	3,700	3,350
7/32	8.30	4,800	4,360
1/4	10.6	6,100	5,600
5/16	16.7	9,000	8,100
3/8	23.6	12,500	11,400





7X19 Stainless Steel Cable

Diameter (in)	Weight per 100ft (lbs)	Nominal B.S. (lbs)	
		AISI 302,304	AISI 316
--	--	--	--
3/32	1.74	920	810
1/8	2.9	1,760	1,530
5/32	4.5	2,400	2,110
3/16	6.5	3,700	3,210
7/32	8.6	5,000	4,350
1/4	11.0	6,400	5,600
5/16	17.3	9,000	8,200
3/8	24.3	12,000	11,000



1X19 Stainless Steel Strand

Diameter (in)	Weight per 100ft (lbs)	Nominal B.S. (lbs)	
		AISI 302,304	AISI 316
1/16	0.85	550	480
3/32	2.00	1,200	1,070
1/8	3.50	2,100	1,760
5/32	5.50	3,300	3,000
3/16	7.70	4,700	4,270
7/32	10.2	6,300	5,730
1/4	13.5	8,200	7,460
5/16	21.0	12,500	11,800
3/8	30.0	17,500	16,500
1/2	54.0	31,000	29,500
9/16	69.0	38,000	36,100
5/8	85.0	47,400	44,970



6X19/37 Class SS Wire Rope

Diameter (in)	Approx. Weight/ft. (lb)	Nominal B.S. (lbs)	
		AISI 302,304	AISI 316
5/16	0.18	9,000	8,200
3/8	0.26	12,000	10,800
7/16	0.35	16,300	14,800
1/2	0.46	22,800	20,500
9/16	0.59	28,500	25,700
5/8	0.72	35,000	31,500
3/4	1.04	49,600	44,600
7/8	1.42	66,500	59,900
1	1.85	85,400	76,900
1-1/8	2.34	106,400	95,800
1-1/4	2.89	129,400	116,500