

Model 430 Specifications

Model numbers shown in green are part of our INSTOCK program.

Model Number	Capacity (tons)	Spread (in.)	HR (in.)	A (in.)	B (in.)	C (in.)	O (in.)	Weight (lbs.)
430-.25-2	1/4	24	23.9	.63	2.80	5	.89	7.6
430-.25-3	1/4	36	29.9	.63	2.80	5	.89	9.6
430-.25-4	1/4	48	35.9	.63	2.80	5	.89	11.9
430-.25-6	1/4	72	47.9	.63	2.80	5	.89	16.3
430-.25-8	1/4	96	59.9	.63	2.80	5	.89	20.4
430-.25-10	1/4	120	71.9	.63	2.80	5	.89	24.7
430-.25-12	1/4	144	85.4	.63	2.80	5	.89	45.5
430-.25-14	1/4	168	98.4	.63	2.80	5	.89	67.2
430-.25-16	1/4	192	110.4	.63	2.80	5	.89	76.1
430-.25-18	1/4	216	122.4	.63	2.80	5	.89	86.1
430-.25-20	1/4	240	134.4	.63	2.80	5	.89	135.6
430-.5-2	1/2	24	23.9	.63	2.80	5	.89	7.5
430-.5-3	1/2	36	30	.63	2.80	5	.89	9.6
430-.5-4	1/2	48	36	.63	2.80	5	.89	11.9
430-.5-6	1/2	72	48	.63	2.80	5	.89	16.3
430-.5-8	1/2	96	61.5	.63	2.80	5	.89	32.3
430-.5-10	1/2	120	74.5	.63	2.80	5	.89	49.1
430-.5-12	1/2	144	86.5	.63	2.80	5	.89	59.2
430-.5-14	1/2	168	98.5	.63	2.80	5	.89	96.2
430-.5-16	1/2	192	110.5	.63	2.80	5	.89	110.4
430-1-2	1	24	23.9	.63	2.8	5	.89	12.6
430-1-3	1	36	30.8	.63	2.8	5	.89	15.1
430-1-4	1	48	36.8	.63	2.8	5	.89	17.9
430-1-6	1	72	50.3	.63	2.8	5	.89	31.4
430-1-8	1	96	63.3	.63	2.8	5	.89	51.1
430-1-10	1	120	75.3	.63	2.8	5	.89	82.6
430-2-2	2	24	26.2	.63	2.80	5	.91	20.6
430-2-3	2	36	32.2	.63	2.80	5	.91	22.7
430-2-4	2	48	39.7	.63	2.80	5	.91	31.2
430-2-6	2	72	52.7	.63	2.80	5	.91	46.5
430-2-8	2	96	64.7	.63	2.80	5	.91	72.8
430-3-2	3	24	27	.63	2.80	5	1.0	22.8
430-3-3	3	36	33	.63	2.80	5	1.0	25.1
430-3-4	3	48	41.4	.63	2.80	5	1.0	39.9
430-3-6	3	72	53.4	.63	2.80	5	1.0	62.5